

VALUE LINE  
WASHER-EXTRACTORS



**SERIOUS ABOUT LAUNDRY.**

**UniMac**<sup>®</sup>



**SERIOUS ABOUT LAUNDRY.**

# VALUE LINE WASHER-EXTRACTORS

UniMac has been recognized around the world as the leading manufacturer of commercial laundry equipment. We produce, sell and support more commercial washers and dryers in North America than any other company. Our value line washer-extractors are renowned for their durability, innovative features, efficient performance and lowest cost of ownership.

Our Value Line washer-extractors are designed to fit your budget while featuring the same durable A-frame design, high quality brass fill valves and versatile supply dispenser as our premium models. Every machine is protected by our standard industry-leading three- and five-year limited parts warranty.

## VALUE LINE WASHER-EXTRACTOR – AT A GLANCE

- 30 programmable cycles
- Doors open at complete 180° angle
- Two ways to program (manual or laptop)
- Real Time Clock records events by date/time
- 30 programmable water levels
- Cylinder rotation sensor
- Up to eight fill segments per cycle
- Temperature controlled fill
- Auto Leak Detection to manage water consumption
- Wash actions programmable, from delicate to heavy soil
- Diagnostic capabilities
- Four supply signals

	UW80	UW100	UW125
Control Options	M30	M30	M30
Capacity - lb (kg)	80 (36.4)	100 (45.5)	125 (56.9)
Width - in (mm)	41 1/2 (1054)	41 1/2 (1054)	48 (1219)
Depth - in (mm)	51 1/2 (1308)	54 1/2 (1384)	58 (1473)
Height - in (mm)	68 1/2 (1740)	68 1/2 (1740)	72 (1829)
Cylinder Diameter - in (mm)	36 (914)	36 (914)	42 (1067)
Cylinder Depth - in (mm)	21 (533)	27 (686)	24 (610)
Cylinder Volume - cu. ft. (liters)	12.4 (350)	15.9 (450)	19.4 (544)
Door Opening - in (mm)	17 1/2 (445)	17 1/2 (445)	20 (508)
Door Bottom to Floor - in (mm)	29 (737)	29 (737)	29 (737)
Water Inlet Connection - in (mm)	3/4 (19)	3/4 (19) (2 ea)	1 (25)
Steam Connection - in (mm)	1/2 (13)	1/2 (13)	3/4 (19)
Drain Diameter - in (mm)	3 (76)	3 (76)	3 (76)
	M Sp	M Sp	M Sp
Motor Size - HP (kW)	7.5 (5.6)	7.5 (5.6)	10 (7.5)
Cylinder Speed RPM (G-Force)	Wash	40 (0.8)	40 (0.8)
	Distribution	70 (2.5)	70 (2.50)
	Very Low Extract	343 (60)	343 (60)
	Low Extract	485 (120)	485 (120)
	Medium Extract	594 (180)	594 (180)
Domestic Shipping Dimensions - in (mm)	Width	44 (1118)	44 (1118)
	Depth	60 1/2 (1537)	60 1/2 (1537)
	Height	77 1/4 (1962)	77 1/4 (1962)
Net Weight - lb (kg)	1730 (785)	1770 (805)	2420 (1100)
Standard Shipping Weight - lb (kg)	1795 (814)	1835 (832)	2525 (1148)
Slat Crate Shipping Weight - lb (kg)	1990 (903)	2030 (921)	2800 (1270)
Agency Approvals	cETLus, CE	cETLus, CE	cETLus, CE

**To learn more, or to find a distributor in your area, visit [UNIMAC.COM](http://UNIMAC.COM)**  
**Alliance Laundry Systems - Shepard St, Ripon WI 54971 - 1.800.587.5458 - 1.920.748.3121**



Consult your UniMac distributor for details. For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management systems at Alliance Laundry Systems' Ripon facility has been registered to ISO 9001:2000.

© 2013 Alliance Laundry Systems LLC. Printed in the U.S.A.



**SERIOUS ABOUT LAUNDRY.**