

ALL-NEW VALUE LINE
WASHER-EXTRACTORS



SERIOUS ABOUT LAUNDRY.

UniMac

WHERE BRAND-NEW MEETS VALUE

UniMac has been recognized around the world as the leading manufacturer of commercial laundry equipment. Our customers are the direct focus of every product we manufacture and every decision we make. We produce, sell and support more commercial washers and dryers in North America than any other company.

Our UW washer-extractors are renowned for their durability, innovative features and industrial strength. Our new Value Line of UW45 & 65 models will provide you with exactly that – all while fitting your budget. They are designed to run 24/7, built for the heaviest OPL use and last longer than ever before. A five-year warranty covers the frame, basket, shaft, bearings and seals from failure or breakage during normal operation due to defects in material or workmanship. A limited three-year warranty is offered on all other parts.

SPECIFICATIONS		UW45		UW65	
Control Options		M30		M30	
Capacity - lb (kg)		45 (20)		65 (30)	
Cylinder Diameter - in (mm)		31" (787)		31" (787)	
Cylinder Depth - in (mm)		16.5" (419)		22" (559)	
Cylinder Volume - cu. ft. (liters)		7.21 (204)		9.61 (272)	
Height - in (mm)		64.50" (1638)		64.50" (1638)	
Width - in (mm)		34.25" (870)		34.25" (870)	
Depth - in (mm)		42.85" (1088)		48.35" (1228)	
Door Opening Size - in (mm)		17.8" (452)		17.8" (452)	
Door Bottom to Floor - in (mm)		28.09" (713)		28.09" (713)	
Motor Size - HP (kW)		5 (3.7)		5 (3.7)	
Total # of Speeds		L Sp	M Sp	L Sp	M Sp
		5	6	5	6
Gentle Wash Distribution Very Low Low Medium	Gentle	30 (0.4)	30 (0.4)	30 (0.4)	30 (0.4)
	Wash	42 (.78)	42 (.78)	42 (.78)	42 (.78)
	Distribution	75 (2.5)	75 (2.5)	75 (2.5)	75 (2.5)
	Very Low	248 (27)	248 (27)	248 (27)	248 (27)
	Low	477 (100)	477 (100)	477 (100)	477 (100)
	Medium	—	674 (200)	—	674 (200)
Drain Diameter - in (mm)		3" (76)		3" (76)	
Steam Connection (Optional) - in (mm)		1/2" (13)		1/2" (13)	
Water Inlet Connection - in (mm)		2 @ 3/4" (19)		2 @ 3/4" (19)	
Shipping Dimensions	Width	37.2" (945)		37.2" (945)	
	Depth	53.8" (1367)		53.8" (1367)	
	Height	65" (1651)		65" (1651)	
Net Weight - lb (kg)		1020 (463)		1060 (481)	
Standard Shipping Weight - lb (kg)		1065 (483)		1105 (501)	
Slate Crate Shipping Weight - lb (kg)		1190 (540)		1230 (558)	
Agency Approvals		ETL, CE		ETL, CE	

Consult your UniMac distributor for details. For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management systems at Alliance Laundry Systems' Ripon facility has been registered to ISO 9001:2000.

©2012 Alliance Laundry Systems LLC. Printed in the U.S.A.

UW SERIES – AT A GLANCE:

- Industrial construction is built to run 24/7
- Helps reduce drying time and increase through-put with a 200 G-Force hardmount
- Bigger motor has 67% more horsepower than cabinet washer-extractors
- Handles unbalanced loads effortlessly
- 34.24" width easily fits through 36" commercial doorways
- 30 programmable cycles
- Perforated cylinder ribs maximize wash action
- Auto leak detection greatly reduces water loss due to valve blockages or failures
- Six bolts with vertical wrench access make installation easier



To learn more, or to find a distributor in your area, visit UNIMAC.COM

Alliance Laundry Systems
Shepard St, Ripon WI 54971
1.800.587.5458



SERIOUS ABOUT LAUNDRY.