



Maximum Performance



**LIGHT COMMERCIAL SIZE.
HEAVY DUTY PERFORMANCE.**

UNIMAC.COM

SMALL CHASSIS WASHERS AND DRYERS

DESIGNED FOR LONG-LASTING, COMMERCIAL USE.

At UniMac®, washers and dryers are considered more than just laundry equipment. They are key players in the success of on-premises laundry facilities. Our equipment is designed to perform in true OPL environments – and we continually innovate to achieve high levels of efficiency, quality and durability. UniMac products are built to work harder and last longer, from the design to the premium-grade components they are constructed of, our products are engineered to withstand the rigors of commercial applications like nothing else on the market. UniMac invests to deliver more in the on-premises laundry industry.



FRONT LOAD WASHER

The UniMac front load washer is energy and water efficient to help reduce operating costs, while fast cycle times and high G-Force extraction ensure maximum throughput.

- Dynamic balancing technology for maximized productivity
- Ultra-High 440 G-Force to maximize moisture removal and minimize dry times
- Less vibration delivers near silent operation
- Extra-large capacity helps to maximize throughput while minimizing costs
- Upgraded bearing protection system ensures worry-free performance.

Electronic Control system features a time-remaining display, six preset cycle buttons, cycle adjustability, additional cycle options and status indicator lights.



TOP LOAD WASHER

Every on-premises laundry facility needs durable equipment that can get laundry done on time and on budget. UniMac's top load washer is the answer to small on-premises laundries or large-scale operations that wish to supplement their current lineup with smaller alternatives.

- Front serviceability provides easy access to all major components from the installed position
- Rugged suspension system to handle bulky loads with ease
- Durable stainless steel tub that is rust resistant and lifetime guaranteed
- Agitator delivers exceptional wash performance.

The E-Mech Control system has a straight forward design that offers simple water temperatures and fabric selections, as well as lights that monitor the wash cycle progress.



COMMERCIAL DRYER

UniMac light commercial on-premises laundry dryers offer extra large drying capacity in a compact size. They also feature unmatched reliability to deliver ultimate productivity.

- Extra large drying capacity allows you to handle sizable loads
- Front serviceability allows easy access to major components
- Smooth baffles for maximum dry air movement

Electronic Control system features a time-remaining display, six preset cycle buttons, cycle adjustability, cycle and moisture level indicator lights.

The E-Mech Control system has a straight forward design that offers simple temperature and fabric selections, as well as cycle status indicator lights.



STACK WASHER-DRYER & STACK DRYER

By stacking the dryer on top of the washer, you gain a large amount of floor space and can place equipment in places that were never before possible. The utility connections are identical to those used in residential-style equipment, and there's no extra work required. Electrical cords are provided in the USA for gas dryers only. In Canada cords are included for both gas and electric dryers.

- Extra-large 7.0 cu.ft (dryer) capacity needs very little space yet easily handles sizable wash loads
- Large door (dryer) opening is 2.06 sq.ft, one of the largest in the industry

Electronic Control system features a time-remaining display, six preset cycle buttons, cycle adjustability, additional cycle options, cycle status and moisture level indicator lights.

The E-Mech Control system has a straight forward design that offers simple temperature and fabric selections, as well as cycle status indicator lights.

PARTS WARRANTY

1. **FRONT LOAD WASHER**
One year – any part on the entire machine.
2. **TOP LOAD WASHER**
Three years – any part on the entire machine
Five years – the transmission assembly
Lifetime – the stainless steel washtub
3. **COMMERCIAL AND STACK DRYER**
Three years – any part on the entire machine
4. **STACK WASHER-DRYER**
One year – any part on the entire machine



Proudly based in Ripon, Wisconsin, USA, UniMac is dedicated to research, development and testing to provide equipment that delivers industrial strength and long-lasting quality. Our products undergo a 5-stage product-development process and are pushed beyond their limits in our state-of-the-art test lab to ensure they exceed the toughest demands of the commercial environment and meet our customers' highest standards.

SMALL CHASSIS WASHERS & DRYERS

| SPECIFICATIONS | FRONT LOAD WASHER | TOP LOAD WASHER | SINGLE DRYER | SINGLE DRYER | STACK DRYER/DRYER | STACK WASHER/DRYER |
|---|---|------------------------------|--|---|---|---|
| Models | UFNE5BJP115TW01 | UWNMN2SP115CW01 | UDEE5BGS173CW01 UDGE5BGS113TW01 | UDEMNRGS173CW01 UDGMNRGS113CW01 | USEMNAGS173TW01 USGMNAGS113TW01 | UTEESASP175TW01 UTGE5ASP115TW01 UTEESASP285CW01 |
| Available Controls | Electronic | Emech | Electronic | Emech | Emech | Electronic |
| Available Control Location | Front | Rear | Front | Rear | Front | Front |
| Capacity - lb (kg) | 21.5 (9.5) | 16 (7.3) | 18 (8.2) | 18 (8.2) | 18 (8.2) | See front control front load washer and dryer specs to the left |
| Cylinder Volume - cu. Ft. (liters) | 3.42 (96.8) | 3.19 (90.3) | 7.0 (198) | 7.0 (198) | 7.0 (198) | |
| Width - in (mm) | 26 7/8 (683) | 25 5/8 (650) | 26 7/8 (683) | 26 7/8 (683) | 26 7/8 (683) | 26 7/8 (683) |
| Depth - in (mm) | 27 3/4 (704) | 28 (711) | 28 (711) | 28 (711) | 29 (737) | 27 3/4 (704) |
| Height - in (mm) | 40 7/16 (1027) | 43 (1092) | 40 7/16 (1027) | 43 (1092) | 78 3/16 (1986) | 78 3/16 (1986) |
| Spin Speed - G-Force (RPM) | 440 (1200) | 150 (710) | N/A | N/A | N/A | See front control front load washer and dryer specs to the left. |
| Motor Size - HP (kw) | Variable Speed Induction 0.9 (0.67) | 1/2 (0.37) | 1/3 (0.25) | 1/3 (0.25) | 1/3 (0.25) | |
| Water Consumption per Cycle - g (l) | 13.68 (51.8) | 28.07 (106) | N/A | N/A | N/A | |
| IWF (Water Factor) | 4.0 | 8.8 | N/A | N/A | N/A | |
| IMEF (Modified Energy Factor) | 2.20 | 1.35 | N/A | N/A | N/A | |
| Available Heat Sources | N/A | N/A | Gas or Electric | Gas or Electric | Gas or Electric | |
| Available Heating Element (Electric W) | N/A | N/A | 5350 @ 240V | 5350 @ 240V | 5350 @ 240V | |
| Gas Inlet Connection - in (mm) | N/A | N/A | 3/8 (9.5) | 3/8 (9.5) | 3/8 (9.5) | |
| Gas Consumption - BTU/Hr | N/A | N/A | 22,500 | 22,500 | 22,500 | |
| Exhaust Outlet Diameter - in (mm) | N/A | N/A | 4 (102) | 4 (102) | 4 (102) | |
| Exhaust Airflow - cfm (liters/sec) | N/A | N/A | 220 (105) | 220 (105) | 220 (105) | |
| Available Water Temperatures | 3 | 3 | N/A | N/A | N/A | |
| Available Cycles | Heavy Duty, Normal Eco, Perm Press, Delicate, Rinse & Spin, Spin Only | Normal, Perm Press, Delicate | Regular, Perm Press, Delicate, Time Dry, Quick Dry, Fluff Up | Normal, Perm Press, Delicate, No Heat | Normal, Perm Press, Delicate, No Heat | |
| Water Pressure - PSI (Bar) | 20-120 (1.4/8.3) | 20-120 (1.4/8.3) | N/A | N/A | N/A | |
| Cycle Indicator Lights | Yes | Yes | Yes | Yes | Yes | |
| Cylinder Finish | Stainless Steel | Stainless Steel | Galvanized | Galvanized | Galvanized | |
| Available Colors | White | White | White | White | White | White |
| Door Type (Solid/Window) | Window | N/A | Solid | Solid | Solid | Window |
| Available Electrical Requirements - (Voltage/Hz/Ph) | 120/60/1 - 15 Amp | 120/60/1 - 15 Amp | Gas: 120/60/1 - 15 Amp Electric: 120/240/60/1 - 30 Amp | Gas: 120/60/1 - 15 Amp Electric: 120/240/60/1 - 30 Amp | Gas: 120/60/1 - 15 Amp Electric: 120/240/60/1 - 30 Amp | See front control front load washer and dryer specs to the left. For Canada Market, only a single electrical cord is provided requiring 120/240/50-60/1ph 40 Amp |
| Net Weight - lb (kg) | 260 (118) | 190 (86) | Elec/Gas 145/150 (66/68) | Elec/Gas 135/140 (61/64) | Elec/Gas 265/275 (120/125) | 390 (177) |
| Shipping Weight - lb (kg) | 270 (122) | 210 (95) | Elec/Gas 155/160 (70/73) | Elec/Gas 145/150 (66/68) | Elec/Gas 280/290 (127/132) | 425 (193) |
| Shipping Width - in (mm) | 30 (762) | 27 1/2 (699) | 29 (737) | 29 (737) | 29 (737) | 29 (737) |
| Shipping Depth - in (mm) | 34 (864) | 30 (762) | 32 3/4 (832) | 32 3/4 (832) | 32 3/4 (832) | 32 3/4 (832) |
| Shipping Height - in (mm) | 45 1/2 (1156) | 44 1/4 (1124) | 45 1/2 (1156) | 45 1/2 (1156) | 80 (2032) | 80 (2032) |
| ADA Compliant | Yes | No | Yes | Yes | No | No |
| Available Agency Approvals | cULUS | cULUS | Elec: cULUS, Gas: cCSAUS | Elec: cULUS, Gas: cCSAUS | Elec: cULUS, Gas: cCSAUS | Elec: cULUS, Gas: cCSAUS |

Note: Not all options are available for all models. Refer to the price list for the available models and options.

** For Canada Market Stack Dryer / Dyer and Stack Washer / Dryer not available with gas.

TO LEARN MORE OR TO FIND A DISTRIBUTOR IN YOUR AREA, VISIT UNIMAC.COM
ALLIANCE LAUNDRY SYSTEMS - SHEPARD ST, RIPON, WI 54971 - 1.800.587.5458

Authorized Distributor:



Consult your UniMac distributor for details. For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management systems at Alliance Laundry Systems are registered to ISO 9001.