

Vended 25-, 30-, 35- and
55-lb Tumble Dryers



VENDED 25-, 30-, 35- AND 55-LB TUMBLE DRYERS

At Huebsch, our priority is making commercial laundry equipment that's perfectly aligned with your business philosophy. In other words, because you believe that profit is the inevitable result of superior efficiency, durability, simplicity and service, that's exactly what we deliver.

What's more, we deliver it in every facet of our products...

INVEST IN ADVANTAGE

Huebsch tumble dryers maximize profits through superior engineering

Higher capacity

Efficiency means drying more loads, faster. That's how Huebsch tumble dryers—offered in 25-, 30-, 35- and 55-lb models—are built to operate. Even our 25-lb model boasts a 7.7 cu ft cylinder to dry large loads.

Optimum efficiency

Huebsch tumble dryers feature an innovative axial airflow process, reducing energy consumption and producing some of the industry's fastest dry times. Faster drying means less time spent at the laundromat and increased customer satisfaction, loyalty and store profits.

Collaborative effort

Huebsch tumble dryers are available in both single and stack pocket configurations to give your store more drying options and make the most of your space.

A CONTEMPORARY STATEMENT PIECE

Designed to convey Huebsch quality and attention to detail



Galaxy™ 600 controls

Integrating Galaxy 600 controls allows for intuitive operation and simple programming throughout your store with revenue-boosting options. Better yet, it means your vended 25-, 30-, 35- and 55-lb tumble dryers are Huebsch Command™-compatible!

Steeled exteriors

Huebsch's stainless-steel doors reduce chipping and incorporate durable latches and hinges to resist wear and keep machines looking sleek.

Polished quality

Chrome handles come standard, and matching chrome doors are also available. The addition of stainless-steel front panels and cylinders gives your machines unparalleled sophistication. Design upgrades ensure your customers know they are using top-quality equipment.

User-friendly

Huebsch models can be configured with a programmable electronic control that delivers drying options through an intuitive user interface. A large, digital display keeps customers aware of the time remaining on their cycle.

WORKS FOR YOU

Set to do the job and stays up to the task

Damage-resistant

Our patented, oblong cylinder perforations enable drywall screws forgotten in pockets to pass harmlessly through machines without damaging the tumblers' sweep sheets or a user's clothing. This damage-resistant advantage—exclusive to Huebsch machines—can be seen in action at www.huebsch.com.

Low maintenance

Large lint compartments reduce time spent emptying and a heavy-duty belt delivers a long life to cut maintenance time and costs.



Activation versatility

All Huebsch models can be configured for coin or card activation, letting you choose the payment method that works best for your business.

UNMATCHED DURABILITY

Built with premium materials and tested to meet the demands of the harshest environments, these commercial-grade machines deliver reliable, efficient operation load after load—and they're backed by Huebsch's standard three-year warranty.*

*Parts only, labor not included. See Huebsch Warranty Bond for specifics.



INTRODUCING

HUEBSCH COMMAND™

Intuitive laundromat data and analytics that are custom-made for the way you operate

Huebsch Command (only available with Galaxy™ 600 controls) lets you use all features of Galaxy controls—and now you can access them remotely, from anywhere in the world with an internet connection!



MULTILEVEL VEND PRICING CHANGES



TIMELY PERFORMANCE DATA



REMOTE START AND SYSTEM MONITORING



SET TIME-OF-DAY/ DAY-OF-WEEK PRICING



SERVICE ALERTS VIA EMAIL OR TEXT



CONFIGURE MACHINES FROM THE CLOUD



URNS PER DAY



100% SUPPORTED AND UPGRADED BY HUEBSCH

Vended 25-, 30-, 35- and 55-lb Tumble Dryers specifications

Models	HT025	HT030	HT035	HT055	
Control Options	<i>Galaxy™ 600, Basic Electronic</i>	<i>Galaxy™ 600, Basic Electronic</i>	<i>Galaxy™ 600, Basic Electronic</i>	<i>Galaxy™ 600, Basic Electronic</i>	
Dry Weight Capacity - lb (kg)	25 (11)	30 (14)	35 (16)	55 (25)	
Width – in (mm)	27.9 (710)	27.9 (710)	31.5 (800)	36.4 (925)	
Depth – in (mm)	39.4 (1000)	45.5 (1155)	45.5 (1155)	53.1 (1350)	
Height – in (mm)	63.9 (1625)	63.9 (1625)	63.9 (1625)	66.7 (1700)	
Cylinder Depth – in (mm)	24 (610)	30 (762)	30 (762)	35 (889)	
Cylinder Diameter – in (mm)	26.5 (673)	26.5 (673)	30 (762)	33 (838)	
Cylinder Volume – cu ft (liters)	7.7 (220)	9.6 (270)	12.3 (350)	17.3 (490)	
Reversing Cylinder	<i>Option</i>	<i>Option</i>	<i>Option</i>	<i>Option</i>	
Door Opening Size – in (mm)	22.7 (576)	22.7 (576)	22.7 (576)	26.9 (683)	
Energy Data	<i>Gas Models: 64,000 Btu/hr Steam Models: 83,500 Btu/hr Electric Models: 12 kW</i>	<i>Gas Models: 73,000 Btu/hr Steam Models: 83,500 Btu/hr Electric Models: 21 kW</i>	<i>Gas Models: 90,000 Btu/hr Steam Models: 103,400 Btu/hr Electric Models: 24 kW</i>	<i>Gas Models: 112,000 Btu/hr Steam Models: N/A Electric Models: 27 kW</i>	
Gas Connections	0.5	0.5	0.5	0.5	
Plumbing Connection – in	0.75	0.75	0.75	N/A	
Air Outlet Diameter – in (mm)	6 (152)	6 (152)	8 (200)	8 (200)	
Motor – HP	Fan 0.5	0.5	0.5	0.5	
	Cylinder 0.3	0.3	0.3	0.5	
Airflow – cfm	500	500	600	700	
Electrical Specifications	Gas and Steam: 100-120V/50/60/1 200-240V/50/60/1/3 440-480V/50/60/3 380-415V/50/60/3 Electric: 200-208V/50/60/1 230-240V/50/60/1 200-208V/50/60/3 230-240V/50/60/3 380V/50/60/3 400-415V/50/60/3 440V/50/60/3 460-480V/50/60/3	Amps: 10 6 3 3 60 53 36 32 19 18 17 15	Amps: 10 6 3 3 104 90 61 52 33 30 29 27	Amps: 10 6 3 3 118 102 69 59 37 34 32 30	Amps: 12 7 3 3 133 116 78 67 42 39 37 34
Shipping Dimensions	Width 30 (760) Depth 43 (1090) Height 67.6 (1720)	30 (760) 49 (1240) 67.6 (1720)	33 (840) 49 (1240) 67.6 (1720)	35.5 (900) 57 (1450) 70.5 (1790)	
Net Weight – lb (kg)	Gas & Steam 300 (135) Electric 310 (140)	320 (145) 330 (150)	340 (155) 350 (160)	430 (195) 440 (200)	
Shipping Weight – lb (kg)	Gas & Steam 310 (140) Electric 330 (150)	320 (145) 350 (160)	360 (165) 370 (170)	470 (215) 480 (220)	
Agency Approvals	CSA	CSA	CSA	CSA	

Tumble dryer models are made to suit a variety of electrical service characteristics. See your Huebsch distributor for specifications.

For further details on installation, refer to Installation, Operation and Maintenance instructions supplied with the tumble dryer.

USA and Canada models are certified by CSA International.

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management system of Alliance Laundry Systems' Ripon facility has been registered to ISO 9001:2000.